

CLAIMS:

1. A biological suspension processing system comprising:
- 5 a suspension treatment device for treating one or more components of a biological suspension;
- a first fluid flow path communicating with the treatment device for introducing a suspension into the treatment device;
- 10 a second fluid flow path communicating with the treatment device for withdrawing a constituent of the suspension from the treatment device; and
- at least one microelectromechanical sensor communicating with one of said fluid flow paths for sensing a selected characteristic of the fluid within the
- 15 flow path.
2. The system of claim 1 in which a sensor senses one or more characteristics selected from the group consisting of flow rate, pH, cell type, cell
- 20 antigenicity, cell concentration, cell count, viscosity, cholesterol, hematocrit, DNA, viral or bacterial presence, pathogen presence, and partial pressure of a selected gas.
- 25 3. The system of claim 1 in which a sensor communicates with the first fluid flow path and generates a signal responsive to one or more selected characteristic of the fluid in the first fluid flow path, the suspension treatment device including a controller adapted to

receive the sensor signal and to control the treatment device in response thereto.

4. The system of claim 1 in which a sensor communicates
5 with said second fluid flow path and generates a signal responsive to a selected characteristic of the fluid in the second fluid flow path, the suspension treatment device including a controller adapted to receive the sensor signal and to control the treatment device in
10 response thereto.

5. The system of claim 1 in which the sensor is adapted to sense the selected characteristic a plurality of
15 times at discrete intervals.

6. The system of claim 5 in which the sensor generates a signal responsive to a selected characteristic of the fluid in the flow path, the suspension treatment device including a controller adapted to receive the sensor
20 signal and to control the treatment device in response thereto.

7. The system of claim 6 in which sensor communicates with the second fluid flow path and senses the
25 approximate quantity or concentration of a selected cell.

8. The system of claim 1 further comprising a container communicating with the second fluid flow path for receiving the withdrawn constituent, the system being
30 adapted to provide tracking information for associating

with the container the particular characteristic sensed by at least one sensor.

9. The system of claim 8 in which the system comprises machine readable or human readable data storage media carried by the container, the data storage media storing information regarding the particular characteristic sensed by at least one sensor.

10. The system of claim 9 in which the data storage media comprises a bar code label on the container.

11. The system of claim 9 in which the data storage media comprises an electronic data storage device.

12. The system of claim 11 in which the electronic data storage device has a non-volatile semiconductor memory.

13. The system of claim 9 in which the data storage media comprises at least one icon carried by the container and representative of the sensed characteristic.

14. The system of claim 9 in which the suspension includes one or more blood components and the blood component withdrawn is a cellular component, and the container is for storing the cellular component withdrawn, and the data storage media includes data regarding the type, quality, purity, quantity or

concentration of the cellular blood component in the container.

15. The system of claim 1 in which the at least one
5 sensor includes a first sensor communicating with the
first fluid flow path and a second sensor communicating
with the second flow path and the treatment device
comprises an apheresis device and the suspension
comprises whole blood, the first sensor sensing platelets
10 to determine a platelet count in the suspension
introduced into the apheresis device and the second
sensor sensing platelets to determine a platelet count in
the second flow path, wherein the system includes a
container communicating with the second flow path for
15 storing blood platelets withdrawn, and the system further
comprises machine readable or human readable data storage
media carried by the container, the data storage media
storing information regarding platelet count sensed by
one or both of said sensors.

20

16. The system of claim 1 in which a sensor communicates
with said second fluid flow path, and said system
includes a container for storing the constituent
withdrawn, the sensor generating a signal responsive to
25 a characteristic of the constituent withdrawn, and the
system includes a data recording device for receiving the
signal and recording data regarding the sensed
characteristic of the constituent withdrawn.

17. The system of claim 16 in which the data recording device comprises a printer for printing a report of the characteristic sensed.

5 18. The system of claim 17 in which the report is in machine readable graphic format.

10 19. The system of claim 16 wherein the container carries a machine readable electronic data storage device, and in which the data recording device is adapted to transfer data regarding the selected characteristic sensed by the sensor to the electronic data storage device.

15 20. The system of claim 19 in which the electronic storage device comprises a non-volatile semiconductor memory.

20 21. A disposable plastic blood component storage container defining an interior compartment for receiving a blood component, and at least one microelectromechanical sensor carried by the container and communicating with the compartment for sensing a selected characteristic of the blood component received therein.

25 22. The container of claim 21 in which the sensor is adapted to sense bacterial presence or pH in the blood component just before it is administered to a patient.

23. The container of claim 21 in which the sensor includes write once, read many times data storage, and is adapted to be read by an automated reading device.

- 5 24. A blood processing system for providing a characterized blood constituent product, the system comprising:

an apheresis device for separating one or more desired cellular blood constituents from a suspension
10 comprising whole blood;

a first fluid flow path communicating with the apheresis device for introducing a suspension comprising whole blood into the device;

a second fluid flow path communicating with the
15 apheresis device for withdrawing at least one desired cellular blood constituent from the device;

a container communicating with the second fluid flow path for receiving the blood constituent withdrawn from the apheresis device;

20 machine readable or human readable data storage media carried by the container;

at least one microelectromechanical sensor communicating with the first fluid flow path for sensing at least one characteristic of the whole blood and for
25 generating at least one electrical signal responsive to said sensing;

at least one microelectromechanical sensor communicating with the second flow path for sensing the quantity of cellular blood constituent withdrawn from the

apheresis device and for generating an electrical signal responsive to said sensing;

a data recorder adapted to receive the electrical signals from the sensors and to record data regarding the sensed characteristics on the data storage media, whereby
5 a user may readily identify the sensed characteristic regarding the whole blood and the quantity of the desired cellular constituent in the container.

10 25. The system of claim 24 including a sensor communicating with the second fluid flow path for sensing the quantity of a non-desired biologic constituent in the flow path and generating an electrical signal responsive to the amount, the data recorder being adapted to receive
15 such signal and record data regarding the quantity of non-desired cellular constituent in the data storage media for access by a user of the product in the container.

20 26. The system of claim 25 in which the non-desired biologic component is a viral constituent.

27. The system of claim 25 in which the non-desired biologic component is a cellular constituent.

25 28. The system of claim 27 wherein the desired cellular blood constituent is platelets or red cells and wherein the non-desired cellular constituent is white cells.

29. The system of claim 24 further comprising a controller adapted to receive the signals from the sensors communicating with the first and second fluid flow paths and to control the apheresis device in response to one or more of such signals to provide a desired cellular blood constituent product characterized by data recorded in the data storage media in accordance with characteristics sensed by the sensors.

10 30. The system of claim 29 in which the desired cellular blood constituent is platelets, red cells, stem cells or white cells.

15 31. The system of claim 24 in which the data storage media comprises machine readable graphics carried on the container.

20 32. The system of claim 31 in which the machine readable graphics comprises a bar code.

33. The system of claim 24 in which the first fluid flow path communicates with the vascular system of a human donor, and the system includes means for generating a human-readable report for the donor containing selected data regarding one or more of the sensed characteristics.

34. A biological suspension processing system comprising:

30 a blood treatment device for treating one or more components of a biological suspension;

a human subject;

a first fluid flow path communicating with the vascular system of the human subject and the treatment device for introducing blood from the human subject into the treatment device;

a second fluid flow path communicating with the treatment device for withdrawing a constituent of the blood from the treatment device;

a third fluid flow path communicating with the treatment device from withdrawing another constituent of the blood from the treatment device; and

at least one microelectromechanical sensor communicating with one of said fluid flow paths for sensing a selected characteristic of the fluid within the flow path.

35. The system of claim 34 in which the sensor generates a signal responsive to one or more selected characteristic of the fluid in one of the fluid flow path, the suspension treatment device including a controller adapted to receive the sensor signal and to control the treatment device in response thereto.

36. The system of claim 35 in which the third fluid flow path communicates with the human subject, the treatment device is adapted to add anticoagulant to the blood in the first fluid flow path, the selected characteristic includes the hematocrit of blood in the first fluid flow path, and the controller controls the addition of anticoagulant into the first fluid flow path.

51

37. The system of claim 35 in which the controller controls the treatment device in response to the signal to avoid one or more deleterious consequences to the human subject.

5

38. The system of claim 35 in which the controller controls the treatment device in response to the signal to withdraw a constituent of desired quality.

10

39. The system of claim 35 in which the controller controls the treatment device in response to the signal to withdraw a constituent of desired quantity.

15

40. The system of claim 35 in which the control controls the treatment device in response to the signal to withdraw a constituent that is depleted of an undesired component.

20

41. The system of claim 40 in which the undesired component is white cells.

25

42. The system of claim 35 in which the controller controls the treatment device in response to the signal to withdraw a desired constituent.

43. The system of claim 42 in which the desired constituent is platelets.

44. The system of claim 42 in which the desired constituent is red cells or plasma.

45. The system of claim 35 in which the sensor senses
5 platelets and the controller controls the treatment
device to withdraw a selected minimum quantity of
platelets.

code	name	code	name	code	name	code	name
01	01	01	01	01	01	01	01
02	02	02	02	02	02	02	02
03	03	03	03	03	03	03	03
04	04	04	04	04	04	04	04
05	05	05	05	05	05	05	05
06	06	06	06	06	06	06	06
07	07	07	07	07	07	07	07
08	08	08	08	08	08	08	08
09	09	09	09	09	09	09	09
10	10	10	10	10	10	10	10
11	11	11	11	11	11	11	11
12	12	12	12	12	12	12	12
13	13	13	13	13	13	13	13
14	14	14	14	14	14	14	14
15	15	15	15	15	15	15	15
16	16	16	16	16	16	16	16
17	17	17	17	17	17	17	17
18	18	18	18	18	18	18	18
19	19	19	19	19	19	19	19
20	20	20	20	20	20	20	20
21	21	21	21	21	21	21	21
22	22	22	22	22	22	22	22
23	23	23	23	23	23	23	23
24	24	24	24	24	24	24	24
25	25	25	25	25	25	25	25
26	26	26	26	26	26	26	26
27	27	27	27	27	27	27	27
28	28	28	28	28	28	28	28
29	29	29	29	29	29	29	29
30	30	30	30	30	30	30	30
31	31	31	31	31	31	31	31
32	32	32	32	32	32	32	32
33	33	33	33	33	33	33	33
34	34	34	34	34	34	34	34
35	35	35	35	35	35	35	35
36	36	36	36	36	36	36	36
37	37	37	37	37	37	37	37
38	38	38	38	38	38	38	38
39	39	39	39	39	39	39	39
40	40	40	40	40	40	40	40
41	41	41	41	41	41	41	41
42	42	42	42	42	42	42	42
43	43	43	43	43	43	43	43
44	44	44	44	44	44	44	44
45	45	45	45	45	45	45	45
46	46	46	46	46	46	46	46
47	47	47	47	47	47	47	47
48	48	48	48	48	48	48	48
49	49	49	49	49	49	49	49
50	50	50	50	50	50	50	50
51	51	51	51	51	51	51	51
52	52	52	52	52	52	52	52
53	53	53	53	53	53	53	53
54	54	54	54	54	54	54	54
55	55	55	55	55	55	55	55
56	56	56	56	56	56	56	56
57	57	57	57	57			